

Description

HydroCoat is a specially formulated, water-based epoxy coating/sealer, with excellent adhesion to both old and fresh GREEN concrete. This product is designed as a tinted coating for smooth and profiled concrete. HydroCoat has a long pot-life, very low odor, good chemical resistance, and dries to a walk-able surface in 4-6 hours at 73°F.

HydroCoat Features & Benefits

- Economical primer/sealer with excellent coverage rates, 350-500 sf/gallon
- >50% solids epoxy by volume
- Provides an excellent, non-dusting surface for ease of cleaning
- Can be applied over fresh, GREEN concrete within hours
- Excellent adhesion to smooth concrete, will not peel
- Excellent resistance to blistering
- V.O.C. compliant and low odor; <50 g/L
- Can be used indoors or outdoors as a primer
- Good resistance to a wide range of chemicals and cleaning products
- User friendly installation; tools can be cleaned with water

Applications as a Primer/Sealer

- Over smooth, fresh or old concrete
- As a sealer for floors & walls
- To help protect concrete floors from oil stains
- As a primer for tile & carpet adhesives, epoxies and urethanes

Product Details

Bulk Packaging	4-Gallon kits			
Color	Clear or Tinted Gray shades, Beige, others contact factory			
Shelf Life	24 months in unopened containers			
Set Time Guidelines		60°F	73°F	90°F
	Pot Life	45 minutes	1 hour	30 minutes
	Foot Traffic	12 hours	6 hours	4-5 hours
Theoretical Coverage of 1-Gal Kit over smooth concrete	350-500 SF (varies with surface texture and porosity)			
Mix Ratio by Volume	3B:1A (clear) 3B:1A (tinted)			
VOC Content	<50g/L per ASTM D-2369-01			

Concrete Preparation

Note that in general ALL substrates must be clean, sound, and have minimum 250psi tensile bond strength when tested per ASTM D4541. Be sure concrete is free from oil, grease, urethane, paint, adhesive, underlayment or any contaminants. **Do not apply to concrete that has hardeners, curing agents, or densifiers.** HydroCoat should not be applied over slabs subject to Hydrostatic Pressure.

CONCRETE FINISH: HydroCoat is designed to go over smooth, power-trowel concrete; without the need to shot blast or scarify surface. If mechanical surface preparation required, use a fine grit mesh.

Mixing & Application

Pre-mix part B (tinted side) prior to adding part A, to get the pigments well mixed and off the bottom of the pail. Scrape corners with a mixing stick to ensure all pigments are loose. Then add part A into part B pail, and mix using a high-speed hand drill, for approximately 1-2 minute or until the mixed material has uniform consistency. Scrap sides of pail to be sure all A+B sides are integrated.

Note: If application requires 2 coats, you can dilute first coat up to 15% with water, to help improve the economics for the job. After mixing, distribute the liquids into roller pan and using nap roller, dip and roll out immediately. The use of an 18" wide nap roller is highly recommended. HydroCoat must be applied in a thin film, roll the material tight, and do not allow material to puddle. Roll slowly using a cross-hatch pattern if necessary. Material will not dry uniformly if allowed to puddle. Re-coat times range 2-6 hours depending on porosity of the surface.

Note: For maximum floor protection, it may be necessary to apply two coats of HydroCoat. This will depend on the porosity of the concrete as well as the amount of protection required.

Clean Up

HydroCoat, while still wet, can be cleaned up with a scouring pad and warm soapy water. If allowed to set, then mechanical cleaning or the application of a suitable paint stripper is required.

Dispose of excess material in accordance with local, state, and federal regulations.

Storage

HydroCoat should be stored in closed containers, between temperatures 50-80°F. Do not allow to freeze.

Safety Precautions

HEALTH CONSIDERATIONS

As with all epoxies, good hygienic habits must be observed, and the wearing of protective clothing and gloves is advised. Before using any S3 Surface Solutions, LLC. product, please read and follow the product Safety Data Sheet (SDS). Use this product only as directed. Keep out of the reach of Children.

FOR YOUR PROTECTION

The data, statements and recommendations set forth in this product information sheet are based on research and development work which has been carefully conducted by S3 Surface Solutions, LLC. and we believe such data, statements and recommendations will serve as reliable guidelines. This product is subject to numerable uses under varying conditions over which we have no control, and accordingly, we do NOT warrant that this product is suitable for any use. Users are advised to test the product in advance to make certain it is suitable for their installation conditions and uses.

DISCLAIMER

The information contained in this Technical Data Sheet (TDS) is correct as of the day issued. S3 Surface Solutions (S3) makes no other representation, warranty or guarantee of any kind, expressed or implied, statutory or otherwise, including without limitation in respect of merchantability, merchantable quality, durability, fitness for a particular purpose, course of performance or usage of trade, howsoever arising. The user is responsible for determining whether the S3's product is durable, fit for a particular purpose or suitable for the user's method of use or application. Given the variety of factors that can affect the use and application of a S3 product, some of which are uniquely within the user's knowledge and control, it is essential that the user firstly evaluate the S3 product to determine whether it is fit for a particular purpose and suitable for the method of use or application.

WARRANTY

The data, statements and recommendations set forth in this product information sheet are based on testing, research and other development work which has been carefully conducted by us, and we believe such data, statements and recommendations will serve as reliable guidelines. However, this product is subject to numerable uses under varying conditions over which we have no control, and accordingly, we do NOT warrant that this product is suitable for any particular use. Users are advised to test the product in advance to make certain it is suitable for their particular production conditions and particular use or uses.

WARRANTY - All products manufactured by us are warranted to be first class material and free from defects in material and workmanship. Liability under this warranty is limited to the net purchase price of any such products proven defective, or, at our option, to the repair or replacement of said products upon their return to us transportation prepaid. All claims hereunder on defective products must be made in writing within 30 days after the receipt of such products in your plant and prior to further processing or combining with other materials and products. WE MAKE NO WARRANTY, EXPRESS OR IMPLIED, AS TO THE SUITABILITY OF ANY OF OUR PRODUCTS FOR ANY PARTICULAR USE, AND WE SHALL NOT BE SUBJECT TO LIABILITY FROM ANY DAMAGES RESULTING FROM THEIR USE IN OPERATIONS NOT UNDER OUR DIRECT CONTROL. THIS WARRANTY IS EXCLUSIVE OF ALL OTHER WARRANTIES.